

[illegible]

SPECIFICATIONS:

Current Rating: 3.0 AMP

Contact Resistance: 30mΩ Max

Insulation Resistance: 1000M Ω Min

Withstand Voltage: 600V AC/minute

Operation Temperature: -40°C to +105°C

MATERIALS

Contact Material: Copper Alloy

Contact Plating: Gold over 50u" Ni

Insulator Material: PBT, Polyester(UL94V-0)

Dimension anitheses list (尺寸对照表)							
Item (项目)	A	B	L	PA	D	W	H
Standard (尺寸)	见左表	见左表	11.50	6.00	0.60	7.40	2.50
参考尺寸 (普通)						7.40	

E					Units mm	Scale	2:1	Drawing By Wei Peng		Shenzhen Jiatel Hardware Electronics Co.,Ltd					
D					Tolerance Unless			Date		www.jiatel.com					
C					Otherwise Specified			Check By Hai Gao		Date 2009/11/17		Title	2.54mm dual row SMT Pin Header with locating Post		
B					增加参考尺寸栏		091201312/23-09	.X ~ ±0.30		Date		Sheet 1 of 1			
A					RELEASED		17/11-09	.XX ~ ±0.25		Approval By Eirczhang		Thirt Angle Projection		Drawing Nd. 3132XXMM141	REV
REVZONE	LTR				DESCRIPTION.		ECN.NO.	Date	Angle ~ ± 3°	Date				File Path L\E\FXTZ\PZXL\2.54PZ	B
1		2		3		4		5		6		7		8	