

1

Contacts	DIM A	DIM B
1	-----	1.27
2	1.27	2.54
3	2.54	3.81
4	3.81	5.08
5	5.08	6.35
6	6.35	7.62
7	7.62	8.89
8	8.89	10.16
9	10.16	11.43
10	11.43	12.70
11	12.70	13.97
12	13.97	15.24
13	15.24	16.51
14	16.51	17.78
15	17.78	19.05
16	19.05	20.32
17	20.32	21.59
18	21.59	22.86
19	22.86	24.13
20	24.13	25.40
21	25.40	26.67
22	26.67	27.94
23	27.94	29.21
24	29.21	30.48
25	30.48	31.75
26	31.75	33.02
27	33.02	34.29
28	34.29	35.56
29	35.56	36.83
30	36.83	38.10
31	38.10	39.37
32	39.37	40.64
33	40.64	41.91
34	41.91	43.18
35	43.18	44.45
36	44.45	45.72
37	45.72	46.99
38	46.99	48.26
39	48.26	49.53
40	49.53	50.80

2

3

4

5

6

SPECIFICATIONS:

- Current Rating: 1.0 AMP
- Contact Resistance: 30mΩ Max
- Insulation Resistance: 1000MΩ Min
- Withstand Voltage: 300V AC/minute
- Operation Temperature: -40°C to +105°C

MATERIALS:

- Contact Material: Copper Alloy
- Contact Plating: Gold or Tin over 50u" Ni
- Insulator Material: Polyester(UL94V-0)

Dimension antitheses list (尺寸对照表)

Item (项目)	A	B	L	PA	PC	W1	H
Dimension (尺寸)	见左表	见左表	XX	2.80	2.60	2.50	2.00/1.50

E						Units mm		Scale 2:1		Drawing By Wei Peng		Shenzhen Jiatel Hardware Electronics Co., Ltd			
D						Tolerance Unless		Date				www.jiatel.com			
C						Otherwise Specified		Check By Hai Gao				Date 2009/10/29		Title 1.27mm Single Row DIP Pin Header	
B						.X ~ ±0.30		Date				Sheet 1 of 1			
A						.XX ~ ±0.25		Approval By Eric Zhang				Third Angle Projection		Drawing Nd. 33X1XS141	
REVZONE		LTR		RELEASED		29/10-09		Date				File Path		L\\E\F\XTZ\1.27PZ	
ECN.NO.		Date		Angle ~ ± 3°								6		7	
1		2		3		4		5		6		7		8	